

# STRIP-N-STICK® 300AR

## Fiberglass Reinforced Sponge Tape

Saint-Gobain Performance Plastics CHR® Strip-N-Stick® 300AR offers the unique construction of a reinforced medium compression COHRLastic® closed cell silicone sponge with an acrylic pressure-sensitive adhesive on one side. SNS 300AR offers superior service life, excellent conformability, and flexibility. Other benefits include low compression set and high adhesion to a variety of substrates. Often chosen for the high and low temperature resistance, gasketing, vibration damping, and thermal insulation.

### Typical Properties

|  |                    |
|--|--------------------|
| Thickness Available (inches)                             | 1/16", 1/8", 3/16" |
| Adhesive Type  | Acrylic            |
| Adhesion (oz./inch width)                                | 30                 |
| Tensile (lbs./inch)                                      | 180                |
| Elongation (%)   | <10                |
| Compression Deflection (comp. 75% of original)           | 15                 |
| Compression Set %<br>(50% compression, 22 hours @ 212°F) | 25                 |
| Adhesive Shelf Life                                      | 24 months          |
| Adhesive Temperature Range (°F)                          | -20 – +325         |
| Color  | Blue/Gray          |

Values shown are typical. Certified test reports for writing specifications are available.

### Availability

Thicknesses of 1/16" and 1/8" are standard 10-yard rolls. Thickness of 3/16" is 5-yards long.

Widths available on all thicknesses range from 1/4" wide up to 35" wide.

All rolls supplied with a release liner on the adhesive side.

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**NOTE:** Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

### Application Advantages

- Dimensional stability of fiberglass reinforcement.
- Elimination of sponge elongation.
- Close tolerance and narrow slitting.
- Instant gasket.
- Odorless, non-corrosive, non-toxic.

**Saint-Gobain Performance Plastics Corporation**  
14 McCaffrey St.  
Hoosick Falls, New York 12090-0320  
**Customer Service: (800) 962-2666**  
Tel: (518) 686-7301  
Fax: (800) 562-8479, (518) 686-4840

[www.fff.saint-gobain.com](http://www.fff.saint-gobain.com)

COHRLastic is a registered trademark.  
©2005 Saint-Gobain Performance Plastics Corporation  
AFF-1392-PDF-0205-SGCS